



# TEREX

# TV800-1 & TV900-1

## Tandem Asphalt Rollers

<b>OPERATING WEIGHT</b>	3,466 / 3,572 lbs (1,572 / 1,620 kg)
<b>NET ENGINE POWER</b>	22 hp (16.5 kW)
<b>STATIC LINEAR LOAD</b>	54.2 / 56.4 lbs/in (8.7 / 10.1 kg/cm)
<b>CENTRIFUGAL FORCE</b>	2,809 / 2,944 lbs (12.5 / 13.1 kN)



# TANDEM ASPHALT ROLLERS

### Operating Data, Standard Equipment

	<b>TV800-1</b>	<b>TV900-1</b>
Operating weight	3,466 lbs (1,572 kg)	3,572 lbs (1,620 kg)
Basic weight	3,188 lbs (1,446 kg)	3,208 lbs (1,455 kg)
Static linear load	54.2 lbs/in (8.7 kg/cm)	56.4 lbs/in (10.1 kg/cm)
Total length	73.2 in (1,860 mm)	73.2 in (1,860 mm)
Total width	34.25 in (870 mm)	38.18 in (970 mm)
Turning radius (inside)	72.83 in (1,850 mm)	72.83 in (1,850 mm)
Total height	90.94 in (2,310 mm)	90.94 in (2,310 mm)
Frame articulation degrees	30°	30°
Frequency (Hz) VPM	2,760/3,120 (46/52 Hz)	2,760/3,120 (46/52 Hz)
Amplitude	.020 in (0.5 mm)	.021 in (0.5 mm)
Centrifugal Force lbs	2,809 lbs (12.5 kN)	2,944 lbs (13.1 kN)
Gradeability % (with vibration on)	30%	30%
Gradeability % (with vibration off)	40%	40%
Drum thickness	.4 in (10 mm)	.4 in (10 mm)

# Tandem Asphalt Rollers

## TV800-1 & TV900-1

### Specifications

Engine	
Manufacturer, model	Kubota, D905
Type	3-cylinder, diesel engine
Power rating at 2,500/3,000 rpm	22 hp (16.5 kW)
Cooling system	Liquid
Electrical System	
Nominal voltage	12 Volt
Battery	770 CCA
Alternator	65 Amp
Hydrostatic Transmission	
Hydrostatic drive. Forward and reverse selected from joystick. Infinitely variable speed control forward and reverse. 0 – 5 mph (0 – 8.0 km/h)	
Drive	
Dual radial piston drive motors.	
Brakes	
<b>Service brake:</b> Hydrostatic drive provides dynamic braking.	
<b>Parking brake:</b> Spring applied failsafe	
Steering	
Heavy duty articulated steering	
Fluid Capacities	
Fuel tank	4.75 gal (18 L)
Hydraulic system (includes tank)	7.4 gal (28 L)
Water tank	22.7 gal (86 L)
Operator's Area	
Open operator's compartment with functional design, excellent all-around visibility and user-friendly operator controls.	
Operator's suspension seat with hydraulic cushioning and lap belt; weight, height and longitudinally adjustable.	


### Standard Features

Vandal protection package
Back-up alarm
2 spring loaded scrapers per drum
Hydraulic test points
Electrical diagnostics system (LED lights)
Tow valve
12 volt battery disconnect
Pressure and gravity water
ROPS

### Optional Features

Folding ROPS
Factory-installed hydraulic hammer includes hammer, valve, hoses and tools.

### Dimensions



### TEREX Construction Americas

8800 Rostin Road  
Southaven, MS 38671  
USA

TEL 662-393-1800  
SALES 866-837-3923  
PARTS & TECH SUPPORT 888-201-6008  
FAX 662-393-1700  
EMAIL sales@terexca.com  
WEB terexca.com

For more information, product demonstration, or details on purchase, lease and rental plans, please contact your local TEREX Distributor.