



RATED OPERATING CAPACITY - 665 LBS | 302 KG

COMPACT TRACK LOADER

R070T

SPECIFICATIONS

OPERATING SPECIFICATIONS

Loader Arms	Radial
Operating Weight	3600 lbs 1633 kg
Shipping Weight	3245 lbs 1472 kg
Ground Pressure @ Operating Weight	3.0 psi 20.7 kPa
Rated Operating Capacity (35% of Tipping Load)	665 lbs 302 kg
Operating Capacity (50% of Tipping Load)	950 lbs 431 kg
Tipping Load	1900 lbs 862 kg
Travel Speed, Maximum	6.5 mph 10.5 kph

ENGINE

Type	Diesel, 3-cylinder, naturally-aspirated
Model	Perkins 403D-15
Displacement	92 in ³ 1.5 L
Gross Power Rating @ 2800 rpm	32.7 hp 25.1 kW
Torque, Peak	64.39 ft-lb 87 Nm
Cooling System	Engine-driven fan and coolant/anti-freeze-filled radiator
Intake Air Cleaner	Dual stage
Emission Controls	Meets all U.S. EPA Tier 4 Final standards

UNDERCARRIAGE



Track Type: General purpose track constructed of rubber compound with embedded co-polymer cords and all-purpose treads. Single row of track drive lugs molded in. Turf Track with smooth tread available as an option.

Track Width	11 in 279 mm
Length of Track on Ground	55 in 1397 mm
Ground Contact Area	1183 in ² .76 m ²
Drive System	Two hydrostatic direct drive sprockets controlled by a single joystick
Track Drive Sprocket	Elevated with low friction, replaceable sprocket rollers
Undercarriage Suspension	2 independent torsion axles per undercarriage
Roller Wheels	12 high-density polyurethane and rubber wheels per track Wheels include sealed bearings
Roller Wheel Diameter	10 in 254 mm

AUXILIARY HYDRAULIC SYSTEM

Pump Capacity	10 gpm 37.9 lpm
System Pressure, Max.	3000 psi 20684 kPa
Controls	Intermittent via joystick button or continuous via console switch, mode selectable via dash-mounted switch
Couplers	Push-to-connect quick couplers mounted on loader arms. Pressure relief valve mounted to coupler block
Cooling System	High efficiency oil cooler beside engine radiator, not stacked

DIMENSIONS



WORKS FOR YOU.™



TEREX®

RATED OPERATING CAPACITY - 665 LBS | 302 KG

COMPACT TRACK LOADER

R070T

ELECTRICAL SYSTEM

Nominal charge	12 V
Battery	630 CCA
Charging system	65 amp alternator
Outlets	1-12 V port inside operator station
Wiring	Pre-wired for all factory-available accessories

OPERATOR STATION

Seat: Adjustable contour vinyl seat with built-in operator presence switch, lap bar and 2-inch | 51 mm wide seat belt. An adjustable suspension seat is optional.

Loader Control: Right-hand pilot hydraulic joystick controls loader lift/lower and tilt, plus intermittent control of auxiliary hydraulic.

Drive control: Left-hand pilot hydraulic joystick controls machine speed and direction.

Engine Speed	Hand-operated throttle lever.
Indicators/Gauges	Engine oil low-pressure light Hydraulic oil high-temperature light Engine high-temperature light Low battery voltage light Hourmeter Fuel gauge
ROPS	Meets SAE J1040 MAY94, ISO 3471
FOPS	Meets SAE J1043 SEPT87, ISO 3449
Illumination	4 - Fixed forward-facing halogen lights 1 - Adjustable rear-facing halogen light 1 - Interior light
Convenience	12 V power port
Horn	
Backup Alarm	

SERVICE REFILL CAPACITIES

Fuel Tank	10 gal 37.9 L
Hydraulic Tank	8 gal 30.3 L
Engine Coolant/Antifreeze	1.5 gal 5.6 L
Engine Oil, Including Filter	6.3 quarts 6 L

OPTIONAL ATTACHMENTS

Auger Drive And Bits	Grapple Bucket
Backhoe	Pallet Forks
Broom, Rotary	Power Box Rake
Bucket, General Purpose	Snow Blade
Bucket, Light Material	Snow Blower
Bucket, Multi-Purpose	Stump Grinder
Brush Cutter, Rotary	Trencher
Dozer Blade	Vibratory Roller
Eliminator Rake	

MACHINE OPTIONS

Cab enclosure with wiper	Cab enclosure with heater, insulation, wiper
Beacon, rotating	Front door, polycarbonate
Sound insulation	Window, rear
Suspension seat, adjustable	Windows, side, sliding
Tach and temp guage	Seat belt, 3-inch 76 mm wide
11 in 279 mm Turf Tracks	Attachement control kit (8 pin electrical connector
Engine block heater: recommended for the applications ≤32° F/0° C	

Terex Construction

8800 Rostin Road
Southaven, MS 38671 USA
Tel +1 | 888 90-TEREX
www.terex.com/construction

Distributed By:

www.terex.com/construction

Effective Date: July 2014. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and Terex makes no other warranty, express or implied. © 2014 Terex Construction. Terex, the Terex Crown design and Works For You are trademarks of Terex Corporation or its subsidiaries.